



TECHNICAL DATA

TEST REPORT

PROPERTIES	TEST METHOD	UNIT	RESULT
Yarn		Denier	1000D
Threads		fd/inch	12*12 X
Total Thickness		mm	0.43
Total Weight		g/m ²	510
Tensile Strength (Cut Strip)	FS # 191 5102	lbf / inch	202/184
Elongation	FS # 191 5102	%	22/24
Tear Strength (Trapezoid)	FS # 191 5136	lbf	54/49
Adhesion Strength	FS # 191 5970	lbf / inch	7 / 6
Gloss		☒ 60°	3

REMARK

Product Name : Euroflex EG Matt 510gms
Application : Backlit Display (Outdoor and Indoor)
Printing Method : UV, Solvent, Eco-Solvent, Latex
Made in Korea

Standard Size: 2.60m,3.20m,4.20m,5.00m x 50m

Durability: 12 months application from Invoice date. Outdoor vertical exposure.

(Depending on the weather and location)

Warranty is a standard manufacturer's warranty that only covers material replacement.

The information provided on this data sheet represents typical physical properties and does not constitute a specification. No liability will be accepted for errors and omissions and under no circumstances shall Flex-Europa be liable for any loss or injury arising directly or as a consequence of the publication of this data sheet .All Flex-Europa vinyl's are sold subject to our Conditions of Sales.

Flex-Europa also retains the right to change sizes and specifications of products without prior notice.

Flex-Europa M. E. (FZC) Tel : +971 6 55 78 200, Fax : +971 6 55 78 300, SHARJAH AIRPORT INT'L FREEZONE, PLOT F3 - 17 P.O BOX 8509, SHARJAH, UAE, info@flex-europa.me

