

Technical Data

SignFlex I



TEST REPORT

PROPERTIES	TEST METHOD	UNIT	RESULT
Total Weight		g/m²	780
Tensile Strength			
(Cut Strip)	FS # 191 5102	lbf/inch	285 / 175
Elongation	FS# 191 5102	%	24/24
Tear Strength			
(Trapezoid)	FS # 191 5136	lbf	105 / 60
Adhesion Strength	FS # 191 5970	lbf/inch	15

REMARKS:

: SignFlex 1 23oz. Product Name

Product Specification : 1000Dx1000D (18x12)

Application : Backlit Display (Outdoor and Indoor)

Printing Method : UV, Solvent, Eco-Solvent, Latex, Self-Adhesive.

Made in Korea

Standard Size: 3.20m x 50m

Durability: 3 years application from Invoice date. Outdoor vertical exposure. (Depending on the

weather and location)

Warranty is a standard manufacturer's warranty that only covers material replacement.

The information provided on this data sheet represents typical physical properties and does not constitute a specification. No liability will be accepted for errors and omissions and under no circumstances shall Flex-Europa be liable for any loss or injury arising directly or as a consequence of the publication of this data sheet .All Flex-Europa vinyl's are sold subject to our Conditions of Sales. Flex-Europa also retains the right to change sizes and specifications of products without prior notice.

Flex-Europa M. E. (FZC) Tel: +971 6 55 78 200, Fax: +971 6 55 78 300, SHARJAH AIRPORT INT'L FREEZONE, PLOT F3 - 17 P.O BOX 8509, SHARJAH, UAE, info@flex-europa.me





















