

TECHNICAL DATA

Eurobanner B-W 510

Description of commodity: Laminated black back 510gsm 1000x1000 9x9			
ITEM	DATA	UNIT	TEST METHOD
Fabric	High tenacity yarns 100%PES(1000D*1000D)		DIN EN ISO2060
Construction	Knitting 9*9	inch	DIN60001
Total weight	510	g/sq.m	DIN53352 BS3424 method5A
Weight of fabric	85	g/sq.m	DIN53352 BS3424 method5B
Weight of pvc coating	425	g/sq.m	DIN53352 BS3424 method5B
Tensile strength	Warp: 1350	N/5cm	DIN53354 BS3424 method6A
	Weft: 1150		
Tearing strength	Warp: 160	Ν	DIN53356 BS3424 method 7A
	Weft: 135		
Adhesion	60	N/5cm	DIN53357 BS3425 method9B
Suitable temperature	-20+70	Ĉ	DIN 53372 BS3424 method10
Flame retardancy	No		
Lacquering	No		
Conclusions and Announcements	Declaration by Flex -Europa: Please choose Flex -Europa products suitable according to relative provisions or industrial standards. Flex -Europa bears the responsibility for the specified technical and performance data on h is page only. Flex-Europa is not responsible for any other liability. (The technical data is calculated on average, and $\pm 5\%$ tolerance is acceptable) Remarks: "G" represents Glossy surface, "M" represents Matte surface, Glossy or Matte could be made as requirements.		

Flex-Europa M. E. (FZC) Tel: +971 6 55 78 200, Fax: +971 6 55 78 300, SHARJAH AIRPORT INT'L FREEZONE, PLOT F3 - 17 P.O. BOX 8509, SHARJAH, UAE, info@flex-europa.me



FL®RA