

Technical Data

SignFlex II



TEST REPORT

PROPERTIES	TEST METHOD	UNIT	RESULT
Total Weight		g/m ²	680
Tensile Strength (Cut Strip)	FS # 191 5102	lbf / inch	145 / 160
Elongation	FS # 191 5102	%	20 / 20
Tear Strength (Trapezoid)	FS # 191 5136	lbf	45 / 35
Adhesion Strength	FS # 191 5970	lbf / inch	15

REMARKS:

Product Name : SignFlex II 20oz.
 Product Specification : 500Dx1000D (18x12)
 Application : Backlit Display (Outdoor and Indoor)
 Printing Method : UV, Solvent, Eco-Solvent, Latex
 Made in Korea

Standard Size: 1.12m,1.22m,1.35m,1.65m,1.84m,2.25m,2.60m,2.80m,3.20m x 50m

Durability: 1-2 years application from Invoice date. Outdoor vertical exposure. (Depending on the weather and location)

Warranty is a standard manufacturer's warranty that only covers material replacement.

The information provided on this data sheet represents typical physical properties and does not constitute a specification. No liability will be accepted for errors and omissions and under no circumstances shall Flex-Europa be liable for any loss or injury arising directly or as a consequence of the publication of this data sheet .All Flex-Europa vinyl's are sold subject to our Conditions of Sales.
Flex-Europa also retains the right to change sizes and specifications of products without prior notice.