

Technical Data

Euroflex SV / Scrimless Vision



TEST REPORT

PROPERTIES	TEST METHOD	UNIT	RESULT
Total Weight		g/m²	550
Tensile Strength (Cut Strip)	FS # 191 5102	lbf/inch	280/280
Elongation	FS # 191 5102	%	25 / 28
Tear Strength (Trapezoid)	FS # 191 5136	lbf	42 / 55
Adhesion Strength	FS # 191 5970	lbf/inch	2

REMARKS:

Product Name : Euroflex SV/Scrimless Vision Flex 550gms

Product Specification : 500Dx500D (40x40)

Application : Backlit Display (Outdoor and Indoor) **Printing Method** : UV, Solvent, Eco-Solvent, Latex

Made in Korea

Standard Size: 1.10m,1.30m,1.60m, 2.20m,2.60m,3.20m x 50m

Durability: 2 Years application from Invoice date. Outdoor vertical exposure.

(Depending on the weather and location)

Warranty is a standard manufacturer's warranty that only covers material replacement.

The information provided on this data sheet represents typical physical properties and does not constitute a specification. No liability will be accepted for errors and omissions and under no circumstances shall Flex-Europa be liable for any loss or injury arising directly or as a consequence of the publication of this data sheet .All Flex-Europa vinyl's are sold subject to our Conditions of Sales. Flex-Europa also retains the right to change sizes and specifications of products without prior notice.

Flex-Europa M. E. (FZC) Tel: +971 6 55 78 200, Fax: +971 6 55 78 300, SHARJAH AIRPORT INT'L FREEZONE, PLOT F3 - 17 P.O BOX 8509, SHARJAH, UAE, info@flex-europa.me





















