

F.E BLOCKOUT 800

Description of commodity: GLP015 Coated blackout 1000D*1000D 20*20 800gsm			
ITEM	DATA	UNIT	TEST METHOD
Fabric	High tenacity yarns 100%PES(1000D)		DIN EN ISO2060
Construction	Weaving 20*20	inch	DIN60001
Total weight	800	g/sq.m	DIN53352 BS3424 method5A
Weight of fabric	170	g/sq.m	DIN53352 BS3424 method5B
Weight of pvc coating	630	g/sq.m	DIN53352 BS3424 method5B
Tensile strength	Warp: 2600	N/5cm	DIN53354 BS3424 method6A
	Weft: 2300		
Tearing strength	Warp: 280	N	DIN53356 BS3424 method 7A
	Weft: 250		
Adhesion	100	N/5cm	DIN53357 BS3425 method9B
Suitable temperature	-20 -----+70	°C	DIN 53372 BS3424 method10
Flame retardancy	As requested.		
Lacquering	As requested.		



FLEX EUROPA 2018

The information provided on this data sheet represents typical physical properties and does not constitute a specification. No liability will be accepted for errors and omissions and under no circumstances shall Flex-Europa be liable for any loss or injury arising directly or as a consequence of the publication of this data sheet .All Flex-Europa vinyl's are sold subject to our Conditions of Sales.

Flex-Europa also retains the right to change sizes and specifications of products without prior notice.

Flex-Europa M. E. (FZC) Tel : +971 6 55 78 200, Fax : +971 6 55 78 300, SHARJAH AIRPORT INT'L FREEZONE, PLOT F3 - 17 P.O BOX 8509, SHARJAH, UAE, info@flex-europa.me