

### TEST REPORT

PROPERTIES	TEST METHOD	UNIT	RESULT
Total Weight		g/m2	610
Tensile Strength (Cut Strip)	FS # 191 5102	lbf / inch	160 / 100
Elongation	FS # 191 5102	%	22 / 24
Tear Strength (Trapezoid)	FS # 191 5136	lbf	36 / 27
Adhesion Strength	FS # 191 5970	lbf / inch	12

### REMARKS:

Product Name : SignFlex III 18oz.  
 Product Specification : 500Dx500D (18x12)  
 Application : Backlit Display (Outdoor and Indoor)  
 Printing Method : UV, Solvent, Eco-Solvent, Latex  
 Made in Korea

Standard Size: 1.12m,1.27m,1.37m,1.62m,1.84m,2.25m,2.60m,2.80m,3.20m x 50m

Durability: 18 months application from Invoice date. Outdoor vertical exposure.

(Depending on the weather and location)

Warranty is a standard manufacturer's warranty that only covers material replacement.

The information provided on this data sheet represents typical physical properties and does not constitute a specification. No liability will be accepted for errors and omissions and under no circumstances shall Flex-Europa be liable for any loss or injury arising directly or as a consequence of the publication of this data sheet .All Flex-Europa vinyl's are sold subject to our Conditions of Sales. Flex-Europa also retains the right to change sizes and specifications of products without prior notice.