FE-Laminator





Flex-Europa M.E.FZC | Sharjah Airport Int'l Freezone | Dubai Proc

Plot F3-17, P.O.Box 8509 Sharjah, UAE Ph: +971 6 55 78 200

Dubai Production City PBU No. B31, P.O.Box 383816 Dubai, UAE Ph: +971 4241 5414



Specifications

| Smart System | Entry |
|-------------------|-------------------------------------|
| Control Panel | Front and Rear |
| Max Lam Width | 1630mm / 64" |
| Max Lam Thickness | 28mm / 1.1" |
| Max Speed | 15m / min |
| Heating | Top Heated |
| Max Temp | 60 Degrees |
| Up and Down | Pneumatic |
| Roller | 15m / min |
| Roller Diameter | Silicon |
| Trimmer Holder | 2 Single and 1 Double Central Blade |
| Power | 1600W |
| N.W. | 200kgs |
| Dimention (LWH) | 2260 x 860 x 900mm |

Functions



Smart Entry - Front panel

Easy to check figures of set temp, real temp, and button speed, as well as find your lamination records in 30 days.

Date and time display.

Up and down button.



Patent roll shafts

Auto locked exchangeable roll shafts.

Upgraded shaft caps and holders can be easily locked and loaded media.



Smart Entry - Rear panel

Run or stop lamination.

Speed statistics, show button speed, which is convenient to adjust machine speed.



Media tension

You can adjust the tension screw to generate extra tension for prints, keep the media in flat.