



E-Jet UV DTF

UV Direct to Film Printer



G +CMYK +W + V



Anti-collision system



HIWIN guide rail



Laminating Device



Self-development



long life



low cost



High precision

Specifications

Model	UV-S604	
Printhead	Epson I3200-U1 / Epson I1600-U1	
Printhead Quantity	3	4
Printing Color	CMYK + W + V	G + CMYK + W + V
Printing Speed	High Speed Mode	360*1440 DPI 8Pass: 6m /h 360*2160 DPI 12Pass: 4m /h
	High Precision Mode	360*1080 DPI 6Pass: 6m /h 360*1440 DPI 8Pass: 5m /h 360*2160 DPI 12Pass: 3m /h
Printing Size	600mm	
RIP Software	Riin / Flexprint / Codlink / Mainstop	
Media Transfer	UV AB Film	
Lamination	Integrated Automatic Laminator	
Ink Curing	Water Cooler + UVLED Lamp (to ensure long-term high-intensity operation)	
Power Supply	220V 50 - 60HZ 200W	
Work Environment	Temperature: 20C - 30 C Humidity: 35% - 65%	
Dimension	1785mm x 864mm x 1590.2mm	
Packaging Dimensions	2360mm x 860mm x 860mm 1.75CBM	



Flex-Europa M.E.FZC

Sharjah Airport Int'l Freezone
Plot F3-17, P.O.Box 8509
Sharjah, UAE
Ph: +971 6 55 78 200

Dubai Production City
PBU No. B31, P.O.Box 383816
Dubai, UAE
Ph: +971 4241 5414

00971 6 55 78 300 info@flex-europa.me www.flex-europa.me