

FPSO







FLEX-EUROPA

# **Mission**

When you are responsible for visual communication to enhance an organization's image, your own image is on the line. From a simple sign to a complet re-imaging project, you want to offer you best – on time thus giving the best value for your money.

We know how powerful visual concepts can be – it is the most important language in creative design discipline, but sometimes even those powerful creative ideas are lost when all this hard work is not truly completed by choosing the wrong products. With this in mind, our experienced team makes sure that each solution offered is the best to achieve the consistency of your image. As our products are supplied only in response to our customer requirements, whether you are a designer, printer, signmaker, visual merchandiser or an end user, you can rely on our se rvice.

Our long-term view is probably one of the keys of our success, which makes us different in our field. Our relations from a customer to a supplier are all long term and we are supportive within our relation ships

# www.flex-europa.me

\*E DREAM OF WONDERS. \* PERFORM THEM

بالجعالين ملي بنالية بعد م مشمول المنام مشمول الم

(a perle

Ultra Production UV Printer

# XTRA 5000/3300/3300L

# Time For eco-friendly, Production and fast Machine

Flora XTRA fast prinitng speed and high definition printing, this type of color UV printer is suitable for professional digital printing companies to print all kinds of materials, such as paper, PVC, advertising banner, mesh fabrics, adhesive vinyl, etc.



A

# **PRODUCT SPECIFICATIONS**

Print         Model         XTRA 5000         XTRA 3300         XTRA 3300           Print Head         8 ~ 16 KM1024i         5 ~ 10 KM1024i           Draft Mode (2 pass.)         315 sqm/h         200 sqm/h         5 ~ 10 KM1024i           Draft Mode (2 pass.)         315 sqm/h         200 sqm/h         5 ~ 10 KM1024i           Draft Mode (2 pass.)         315 sqm/h         200 sqm/h         5 ~ 10 KM1024i           Draft Mode (2 pass.)         166 sqm/h         100 sqm/h         100 sqm/h           Express (4 pass.)         166 sqm/h         100 sqm/h         73 sqm/h           Print resolution (6 pass.)         80 sqm/h         73 sqm/h         45 sqm/h           Uality (8 pass.)         45 sqm/h         40 sqm/h         40 sqm/h           High (12 pass.)         45 sqm/h         40 sqm/h         40 sqm/h           Technology         Piezoelectric print Head, Gray Scale Technology         1           Ink type         UV LED Curable ink         2.5 L         2.5 L           Color         Standard CMYK, LC LM, White (optional)         CMYK Plus white           Ink Catridge size         5 L         2.5 L         2.5 L           Color         Industrial grade feeding and take-up system         Rold Hadling         Industrid grade feeding and take-up sys	Model         XTRA 5000         XTRA 3300         XTRA 3300           Print Head         8 ~ 16 KM1024i         5 ~ 10 KM1024i           Draft Mode (2 pass)         315 sqm/h         200 sqm/h           Express (4 pass)         166 sqm/h         100 sqm/h         100 sqm/h           Print resolution (6 pass)         80 sqm/h         73 sqm/h         73 sqm/h           Quality (8 pass)         62 sqm/h         54 sqm/h         54 sqm/h           Quality (8 pass)         63 sqm/h         40 sqm/h         40 sqm/h           Print resolution         363 x720, 363 x1080, 726 x720, 726 x1080, 726 x1440         726 x1440           Print resolution         363 x720, 363 x1080, 726 x720, 726 x1080, 726 x1440         726 x1440           Print resolution         363 x720, 363 x1080, 726 x720, 726 x1080, 726 x1440         726 x1440           Technology         Piezoelectric print Head, Gray Scale Technology         726 x1440           Ink type         UV LED Curable ink         725 L           Color         Standard CMYK, LC LM, White (optional)         CMYK Plus white           Ink fare fared perocess Software         photo print Flora Edition 10.5, Caldera, Onyx         725 L           Media / Handling         Industrial grade feeding and take-up system         760 x 200 x 210 cm         580 x 160 x 93 cm					
Print Head         8 ~ 16 KM 1024i         5 ~ 10 KM 1024i           Draft Mode (2 pass)         315 sqm/h         200 sqm/h           Express (4 pass)         166 sqm/h         100 sqm/h         100 sqm/h           Print Mode (2 pass)         166 sqm/h         100 sqm/h         100 sqm/h           Express (4 pass)         166 sqm/h         100 sqm/h         73 sqm/h           Print fesolution         80 sqm/h         54 sqm/h         54 sqm/h           Quality (8 pass)         62 sqm/h         40 sqm/h         40 sqm/h           High (12 pass)         45 sqm/h         40 sqm/h         40 sqm/h           Print resolution         363x720, 363x1080, 726x720, 726x1080, 726x1440         726x1440           Technology         Piezoelectric print Head, Gray Scale Technology         Ink type           Ink type         UV LED Curable ink         Color         Standard CMYK, LC LM, White (optional)         CMYK Plus white           Ink Cartridge size         5 L         2.5 L         2.5 L         2.5 L           color managment         ICC based color managment, adjustable printing curve and den         file format         TIFF, JPEG, Postscrip, EPS, PDF, etc.         Interfaces         Fast standard USB Port         Interfaces         Fast standard USB Port         S000 KG         3600 KG         200 k	Print Head         8 ~ 16 KM1024i         5 ~ 10 KM1024i           Draft Mode (2 pass)         315 sqm/h         200 sqm/h           Express (4 pass)         166 sqm/h         100 sqm/h           Production (6 pass)         80 sqm/h         73 sqm/h         73 sqm/h           Quality (8 pass)         62 sqm/h         54 sqm/h         74 sqm/h           Quality (8 pass)         62 sqm/h         40 sqm/h         40 sqm/h           Print resolution         363x720, 363x1080, 726x720, 726x1080, 726x1440           Print resolution         363x720, 363x1080, 726x720, 726x1080, 726x1440           Technology         Piezoelectric print Head, Gray Scale Technology           Ink type         UV LED Curable ink           Color         Standard CMYK, LC LM, White (optional)         CMYK Plus white           Ink Cartridge size         5 L         2.5 L           color managment         ICC based color managment, adjustable printing curve and den           file format         TIFF, JPEG, Postscrip, EPS, PDF, etc.           Image Process Software         photo print Flora Edition 10.5, Caldera, Onyx           Media / Handling         Industrial grade feeding and take-up system           Roll Media support         Max width500, 330cm, diameter 40cm, weight 360kg           Connectivity         3600 KG         <	Print				
Draft Mode (2 pass)         315 sqm/h         200 sqm/h           Express (4 pass)         166 sqm/h         100 sqm/h         100 sqm/h           Production (6 pass)         80 sqm/h         73 sqm/h         73 sqm/h           Quality (8 pass)         62 sqm/h         54 sqm/h         54 sqm/h           High (12 pass)         45 sqm/h         40 sqm/h         40 sqm/h           Print resolution         363x720, 363x1080, 726x720, 726x1080, 726x1440         Technology           Print resolution         363x720, 363x1080, 726x720, 726x1080, 726x1440         Technology           Ink type         UV LED Curable ink         Color         Standard CMYK, LC LM, White (optional)         CMYK Plus white           Ink Cartridge size         5 L         2.5 L         2.5 L         color           color managment         ICC based color managment, adjustable printing curve and dent         file format         TIFF, JPEG, Postscrip, EPS, PDF, etc.         Image Process Software         photo print Flora Edition 10.5, Caldera, Onyx         Media / Handling         Industrial grade feeding and take-up system         Roll Media support         Max width500, 330cm, diameter 40cm, weight 360kg         200 kG         200 kG         2200 kG         220 kG	Draft Mode (2 pass)         315 sqm/h         200 sqm/h           Express (4 pass)         166 sqm/h         100 sqm/h         100 sqm/h           Production (6 pass)         80 sqm/h         73 sqm/h         73 sqm/h           Quality (8 pass)         62 sqm/h         54 sqm/h         54 sqm/h           Quality (8 pass)         62 sqm/h         40 sqm/h         40 sqm/h           High (12 pass)         45 sqm/h         40 sqm/h         40 sqm/h           Print resolution         363x720, 363x1080, 726x720, 726x1080, 726x1440           Technology         Piezoelectric print Head, Gray Scale Technology           Ink type         UV LED Curable ink           Color         Standard CMYK, LC LM, White (optional)         CMYK Plus white           Ink type         UV LED carable ink         2.5 L           color managment         ICC based color managment, adjustable printing curve and dent           file format         TIFF, JPEG, Postscrip, EPS, PDF, etc.           Image Process Software         photo print Flora Edition 10.5, Caldera, Onyx           Media / Handling         Industrial grade feeding and take-up system           Roll Media support         Max width500, 330cm, diameter 40cm, weight 360kg           Connectivity         S000 KG         3600 KG         2200 KG	Model	XTRA 5000	XTRA 3300	XTRA 3300L	
Express (4 pass)       166 sqm/h       100 sqm/h       100 sqm/h         Production (6 pass)       80 sqm/h       73 sqm/h       73 sqm/h         Quality (8 pass)       62 sqm/h       54 sqm/h       54 sqm/h         Quality (8 pass)       45 sqm/h       40 sqm/h       40 sqm/h         High (12 pass)       45 sqm/h       40 sqm/h       40 sqm/h         Print resolution       363x720, 363x1080, 726x720, 726x1080, 726x1440         Print resolution       363x720, 363x1080, 726x720, 726x1080, 726x1440         Technology       Piezoelectric print Head, Gray Scale Technology         Ink type       UV LED Curable ink         Color       Standard CMYK, LC LM, White (optional)       CMYK Plus white         Ink Cartridge size       5 L       2.5 L         color managment       ICC based color managment, adjustable printing curve and dens         file format       TIFF, JPEG, Postscrip, EPS, PDF, etc.         Image Process Software       photo print Flora Edition 10.5, Caldera, Onyx         Media / Handling       Industrial grade feeding and take-up system         Roll Media support       Max widtb500, 330cm, diameter 40cm, weight 360kg         Connectivity       5000 KG       3600 KG       2200 KG         Printer       790 x 200 x 210 cm       510 x 200 x 210 cm	Express (4 pass)166 sgm/h100 sgm/h100 sgm/hProduction (6 pass)80 sgm/h73 sgm/h73 sgm/hQuality (8 pass)62 sgm/h54 sgm/h54 sgm/hHigh (12 pass)45 sgm/h40 sgm/h40 sgm/hPrint resolution363x720, 363x1080, 726x720, 726x1080, 726x1440TechnologyPiezoelectric print Head, Gray Scale TechnologyInk typeUV LED Curable inkColorStandard CMYK, LC LM, White (optional)CMYK Plus whiteInk Cartridge size5 L2.5 Lcolor managmentICC based color managment, adjustable printing curve and densefile formatTIFF, JPEG, Postscrip, EPS, PDF, etc.Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityFast standard USB PortDimensions5000 KGWeight5000 KGSystem4500WSystem4500WSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz.25A system, 25A UV lampAir0.8 Mpa	Print Head	8 ~ 16 k	(M1024i	5 ~ 10 KM1024i	
Production (6 pass)       80 sqm/h       73 sqm/h       73 sqm/h         Quality (8 pass)       62 sqm/h       54 sqm/h       54 sqm/h         High (12 pass)       45 sqm/h       40 sqm/h       40 sqm/h         Print resolution       363x720, 363x1080, 726x720, 726x1080, 726x1440         Technology       Piezoelectric print Head, Gray Scale Technology         Ink type       UV LED Curable ink         Color       Standard CMYK, LC LM, White (optional)       CMYK Plus white         Ink Cartridge size       5 L       2.5 L         color managment       ICC based color managment, adjustable printing curve and dens         file format       TIFF, JPEG, Postscrip, EPS, PDF, etc.         Image Process Software       photo print Flora Edition 10.5, Caldera, Onyx         Media / Handling       Industrial grade feeding and take-up system         Roll Media supp-rt       Max widtb500, 330cm, diameter 40cm, weight 360kg         Connectivity       Fast standard USB Port         Dimensions       1000 KG       3600 KG       2200 KG         Weight       5000 KG       3600 KG       2200 KG         Weight       5000 W       3600 W       2200 KG         System       4500W       210 to 230VAC, 2 single phase, 50/60Hz, 25A system, 25A UV lamp	Production (6 pass)       80 sqm/h       73 sqm/h       73 sqm/h         Quality (8 pass)       62 sqm/h       54 sqm/h       54 sqm/h         High (12 pass)       45 sqm/h       40 sqm/h       40 sqm/h         Print resolution       363x720, 363x1080, 726x720, 726x1080, 726x1440         Print resolution       363x720, 363x1080, 726x720, 726x1080, 726x1440         Technology       Piezoelectric print Head, Gray Scale Technology         Ink type       UV LED Curable ink         Color       Standard CMYK, LC LM, White (optional)       CMYK Plus white         Ink Cartridge size       5 L       2.5 L         color managment       ICC based color managment, adjustable printing curve and dens         file format       TIFF, JPEG, Postscrip, EPS, PDF, etc.         Image Process Software       photo print Flora Edition 10.5, Caldera, Onyx         Media / Handling       Industrial grade feeding and take-up system         Roll Media support       Max width500, 330cm, diameter 40cm, weight 360kg         Connectivity       Fast standard USB Port         Dimensions       5000 KG       3600 KG       2200 KG         Weight       5000 KG       3600 KG       2200 KG         Weight       5000 KG       3600 KG, 2 single phase, 50/60Hz. 25A system, 25A UV lamp <td< td=""><td>Draft Mode (2 pass )</td><td colspan="2">315 sqm/h 200 sqm/h</td><td></td></td<>	Draft Mode (2 pass )	315 sqm/h 200 sqm/h			
Quality (8 pass)62 sqm/h54 sqm/h54 sqm/hHigh (12 pass)45 sqm/h40 sqm/h40 sqm/hPrint resolution363x720, 363x1080, 726x720, 726x1080, 726x1440TechnologyPiezoelectric print Head, Gray Scale TechnologyInk typeUV LED Curable inkColorStandard CMYK, LC LM, White (optional)CMYK Plus whiteInk Cartridge size5 L2.5 Lcolor managmentICC based color managment, adjustable printing curve and densfile formatTIFF, JPEG, Postscrip, EPS, PDF, etc.Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivitySoo0 KG3600 KGPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeightS000 KGSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp	Quality (8 pass)62 sqm/h54 sqm/h54 sqm/hHigh (12 pass)45 sqm/h40 sqm/h40 sqm/hPrint resolution363x720, 363x1080, 726x720, 726x1080, 726x1440TechnologyPiezoelectric print Head, Gray Scale TechnologyInk typeUV LED Curable inkColorStandard CMYK, LC LM, White (optional)CMYK Plus whiteInk Cartridge size5 L2.5 Lcolor managmentICC based color managment, adjustable printing curve and densifile formatTIFF, JPEG, Postscrip, EPS, PDF, etc.Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityFast standard USB PortDimensions5000 KGWeight5000 KGSystem3600 KGPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KGSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz, 25A system, 25A UV lampAir0.8 Mpa	Express (4 pass )	166 sqm/h	100 sqm/h	100 sqm/h	
High (12 pass)45 sqm/h40 sqm/h40 sqm/hPrint resolution363x720, 363x1080, 726x720, 726x1080, 726x1440TechnologyPiezoelectric print Head, Gray Scale TechnologyInk typeUV LED Curable inkColorStandard CMYK, LC LM, White (optional)CMYK Plus whiteInk Cartridge size5 L2.5 Lcolor managmentICCC based color managment, adjustable printing curve and densfile formatTIFF, JPEG, Postscrip, EPS, PDF, etc.Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityFast standard USB PortDimensions5000 KGPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KGSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp	High (12 pass)       45 sqm/h       40 sqm/h       40 sqm/h         Print resolution       363x720, 363x1080, 726x720, 726x1080, 726x1440         Technology       Piezoelectric print Head, Gray Scale Technology         Ink type       UV LED Curable ink         Color       Standard CMYK, LC LM, White (optional)       CMYK Plus white         Ink Cartridge size       5 L       2.5 L         color managment       ICC based color managment, adjustable printing curve and densi         file format       TIFF, JPEG, Postscrip, EPS, PDF, etc.         Image Process Software       photo print Flora Edition 10.5, Caldera, Onyx         Media / Handling       Industrial grade feeding and take-up system         Roll Media support       Max width500, 330cm, diameter 40cm, weight 360kg         Connectivity       Fast standard USB Port         Dimensions       5000 KG       3600 KG       2200 KG         Printer       790 x 200 x 210 cm       610 x 200 x 210 cm       580 x 160 x 93 cm         Weight       5000 KG       3600 KG       2200 KG         Power       5000W       System       4500W         System       4500W       25A system, 25A UV Iamp       25A system, 25A UV Iamp         Air       0.8 Mpa       0.8 Mpa       0.8 Mpa	Production (6 pass )	80 sqm/h	73 sqm/h	73 sqm/h	
Print resolution363x720, 363x1080, 726x720, 726x1080, 726x1440TechnologyPiezoelectric print Head, Gray Scale TechnologyInk typeUV LED Curable inkColorStandard CMYK, LC LM, White (optional)CMYK Plus whiteInk Cartridge size5 L2.5 Lcolor managmentICC based color managment, adjustable printing curve and densfile formatTIFF, JPEG, Postscrip, EPS, PDF, etc.Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityInterfacesPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KG3600 KG2200 KGPowerUV LampSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp	Print resolution363x720, 363x1080, 726x720, 726x1080, 726x1440TechnologyPiezoelectric print Head, Gray Scale TechnologyInk typeUV LED Curable inkColorStandard CMYK, LC LM, White (optional)CMYK Plus whiteInk Cartridge size5 L2.5 Lcolor managmentICC based color managment, adjustable printing curve and densifile formatTIFF, JPEG, Postscrip, EPS, PDF, etc.Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityInterfacesInterfacesFast standard USB PortDimensions5000 KGPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KGSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lampAir0.8 Mpa	Quality (8 pass )	62 sqm/h	54 sqm/h	54 sqm/h	
TechnologyPiezoelectric print Head, Gray Scale TechnologyInk typeUV LED Curable inkColorStandard CMYK, LC LM, White (optional)CMYK Plus whiteInk Cartridge size5 L2.5 Lcolor managmentICC based color managment, adjustable printing curve and densfile formatTIFF, JPEG, Postscrip, EPS, PDF, etc.Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityInterfacesInterfacesFast standard USB PortDimensions5000 KGYeight5000 KGSouow3600 KGSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp	TechnologyPiezoelectric print Head, Gray Scale TechnologyInk typeUV LED Curable inkColorStandard CMYK, LC LM, White (optional)CMYK Plus whiteInk Cartridge size5 L2.5 Lcolor managmentICC based color managment, adjustable printing curve and densitfile formatTIFF, JPEG, Postscrip, EPS, PDF, etc.Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemHandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityInterfacesInterfacesFast standard USB PortDimensions900 KGPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KGSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A UV IampAir0.8 Mpa	High (12 pass )	45 sqm/h	40 sqm/h	40 sqm/h	
Ink typeUV LED Curable inkColorStandard CMYK, LC LM, White (optional)CMYK Plus whiteInk Cartridge size5 L2.5 Lcolor managmentICC based color managment, adjustable printing curve and densfile formatTIFF, JPEG, Postscrip, EPS, PDF, etc.Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityInterfacesPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KGSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp	Ink typeUV LED Curable inkColorStandard CMYK, LC LM, White (optional)CMYK Plus whiteInk Cartridge size5 L2.5 Lcolor managmentICC based color managment, adjustable printing curve and densitefile formatTIFF, JPEG, Postscrip, EPS, PDF, etc.Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityInterfacesPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KG3600 KG2200 KGPowerVUV Lamp System5000WSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A UV lampAir0.8 Mpa	Print resolution	363x720	, 363x1080, 726x720, 726x1	080, 726x1440	
ColorStandard CMYK, LC LM, White (optional)CMYK Plus whiteInk Cartridge size5 L2.5 Lcolor managmentICC based color managment, adjustable printing curve and densfile formatTIFF, JPEG, Postscrip, EPS, PDF, etc.Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityInterfacesPrinter790 x 200 x 210 cmPrinter790 x 200 x 210 cmMeight5000 KGSouo KG3600 KGPowerLumpVV LampS000WSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp	ColorStandard CMYK, LC LM, White (optional)CMYK Plus whiteInk Cartridge size5 L2.5 Lcolor managmentICC based color managment, adjustable printing curve and densitfile formatTIFF, JPEG, Postscrip, EPS, PDF, etc.Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityInterfacesInterfacesFast standard USB PortDimensions5000 KGPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KG90 x 200 x 210 cm610 or 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lampAir0.8 Mpa	Technology	Piezoele	ctric print Head, Gray Scale	Technology	
Ink Cartridge size5 L2.5 Lcolor managmentICC based color managment, adjustable printing curve and densfile formatTIFF, JPEG, Postscrip, EPS, PDF, etc.Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityInterfacesPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KG3600 KG2200 KGPowerUV Lamp System RequirmentUV Lamp System5000W 4500WSystem, 25A UV lamp50/60Hz. 25A system, 25A UV lamp	Ink Cartridge size5 L2.5 Lcolor managmentICC based color managment, adjustable printing curve and densitfile formatTIFF, JPEG, Postscrip, EPS, PDF, etc.Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemHandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityInterfacesPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KG3600 KG2200 KGPowerUV LampSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lampAir0.8 Mpa	Ink type	UV LED (	Curable ink		
color managment       ICC based color managment, adjustable printing curve and dens         file format       TIFF, JPEG, Postscrip, EPS, PDF, etc.         Image Process Software       photo print Flora Edition 10.5, Caldera, Onyx         Media / Handling       Industrial grade feeding and take-up system         Roll Media support       Max width500, 330cm, diameter 40cm, weight 360kg         Connectivity       Fast standard USB Port         Interfaces       Fast standard USB Port         Dimensions       5000 KG       3600 KG       2200 KG         Power       Veight       5000 KG       3600 KG       2200 KG         VV Lamp       5000W       4500W       Requirment       Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp	color managment       ICC based color managment, adjustable printing curve and densite         file format       TIFF, JPEG, Postscrip, EPS, PDF, etc.         Image Process Software       photo print Flora Edition 10.5, Caldera, Onyx         Media / Handling       Industrial grade feeding and take-up system         Roll Media support       Max width500, 330cm, diameter 40cm, weight 360kg         Connectivity       Interfaces         Printer       790 x 200 x 210 cm       610 x 200 x 210 cm       580 x 160 x 93 cm         Weight       5000 KG       3600 KG       2200 KG         Power       UV Lamp       5000W       3600 KG       2200 KG         Veight       5000 KG       3600 KG       2200 KG         Air       0.8 Mpa       4500W Iang       50/60Hz.	Color	Standard CMYK, LC	LM, White (optional)	CMYK Plus white	
file format       TIFF, JPEG, Postscrip, EPS, PDF, etc.         Image Process Software       photo print Flora Edition 10.5, Caldera, Onyx         Media / Handling       Industrial grade feeding and take-up system         Roll Media support       Max width500, 330cm, diameter 40cm, weight 360kg         Connectivity       Interfaces         Printer       790 x 200 x 210 cm       610 x 200 x 210 cm       580 x 160 x 93 cm         Weight       5000 KG       3600 KG       2200 KG         Power       UV Lamp       5000W       3600 W         System       4500W       Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz.         25A system, 25A UV lamp       25A system, 25A UV lamp	file format       TIFF, JPEG, Postscrip, EPS, PDF, etc.         Image Processs Software       photo print Flora Edition 10.5, Caldera, Onyx         Media / Handling       Industrial grade feeding and take-up system         Roll Media support       Max width500, 330cm, diameter 40cm, weight 360kg         Connectivity       Interfaces         Printer       790 x 200 x 210 cm       610 x 200 x 210 cm       580 x 160 x 93 cm         Weight       5000 KG       3600 KG       2200 KG         Power       UV Lamp       5000W       3600 KG       2200 KG         UV Lamp       5000W       800W       Requirment       Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp         Air       0.8 Mpa       0.8 Mpa       0.8 Mpa	Ink Cartridge size	5	5 L	2.5 L	
Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemHandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityInterfacesInterfacesFast standard USB PortDimensions5000 KGPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KG90 wer3600 KGUV Lamp5000WSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp	Image Process Softwarephoto print Flora Edition 10.5, Caldera, OnyxMedia / HandlingIndustrial grade feeding and take-up systemHandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityInterfacesInterfacesFast standard USB PortDimensions5000 KGPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KG3600 KG2200 KGPowerUV LampSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lampAir0.8 Mpa	color managment	ICC based color managment, adjustable printing curve and density			
Media / Handling       Industrial grade feeding and take-up system         Roll Media support       Max width500, 330cm, diameter 40cm, weight 360kg         Connectivity       Max width500, 330cm, diameter 40cm, weight 360kg         Interfaces       Fast standard USB Port         Dimensions       For S80 x 160 x 93 cm         Printer       790 x 200 x 210 cm       610 x 200 x 210 cm       580 x 160 x 93 cm         Weight       5000 KG       3600 KG       2200 KG         Power       UV Lamp       5000W       3600 W         System       4500W       Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp	Media / Handling       Industrial grade feeding and take-up system         Roll Media support       Max width500, 330cm, diameter 40cm, weight 360kg         Connectivity       Max width500, 330cm, diameter 40cm, weight 360kg         Interfaces       Fast standard USB Port         Dimensions       Fast standard USB Port         Printer       790 x 200 x 210 cm       610 x 200 x 210 cm       580 x 160 x 93 cm         Weight       5000 KG       3600 KG       2200 KG         Power       VV Lamp       5000W       3600 W         System       4500W       Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp         Air       0.8 Mpa       0.8 Mpa	file format	TIFF, JPEG, Postscrip, EPS, PDF, etc.			
HandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityInterfacesInterfacesFast standard USB PortDimensions580 x 160 x 93 cmPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KG3600 KG2200 KGPowerUV Lamp SystemUV Lamp Requirment5000W Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp	HandlingIndustrial grade feeding and take-up systemRoll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityConnectivityInterfacesFast standard USB PortDimensionsDimensionsPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KG3600 KG2200 KGPowerUV Lamp System 4500W Requirment5000W Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lampAir0.8 Mpa	Image Process Softwa	vare photo print Flora Edition 10.5, Caldera, Onyx			
Roll Media support       Max width500, 330cm, diameter 40cm, weight 360kg         Connectivity       Interfaces       Fast standard USB Port         Dimensions       Fast standard USB Port         Printer       790 x 200 x 210 cm       610 x 200 x 210 cm       580 x 160 x 93 cm         Weight       5000 KG       3600 KG       2200 KG         Power       UV Lamp       5000W       System       4500W         Requirment       Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp	Roll Media supportMax width500, 330cm, diameter 40cm, weight 360kgConnectivityInterfacesFast standard USB PortDimensionsS80 x 160 x 93 cmPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KG3600 KG2200 KGPowerUV Lamp5000WSystem4500WUV Lamp5000WSystem, 25A UV lampAirAir0.8 Mpa	Media / Handling				
ConnectivityInterfacesFast standard USB PortDimensionsFinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KG3600 KG2200 KGPowerUV Lamp5000WSystem4500WSystem4500WInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp	ConnectivityInterfacesFast standard USB PortDimensionsPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KG3600 KG2200 KGPowerUV Lamp5000Wsystem4500WSystem4500WInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lampAir0.8 Mpa	Handling	Industrial grade feeding and take-up system			
InterfacesFast standard USB PortDimensionsPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KG3600 KG2200 KGPowerUV Lamp5000Wstandard USB PortSystem4500Wstandard USB PortRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp	Interfaces         Fast standard USB Port           Dimensions         610 x 200 x 210 cm         580 x 160 x 93 cm           Printer         790 x 200 x 210 cm         610 x 200 x 210 cm         580 x 160 x 93 cm           Weight         5000 KG         3600 KG         2200 KG           Power         UV Lamp         5000W         System         4500W           Requirment         Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp         Solder Lamp           Air         0.8 Mpa         Solder Lamp         Solder Lamp         Solder Lamp	Roll Media support	Max width500, 330cm, diameter 40cm, weight 360kg			
InterfacesFast standard USB PortDimensionsPrinter790 x 200 x 210 cm610 x 200 x 210 cm580 x 160 x 93 cmWeight5000 KG3600 KG2200 KGPowerUV Lamp5000Wstandard USB PortSystem4500Wstandard USB PortRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp	Interfaces         Fast standard USB Port           Dimensions         610 x 200 x 210 cm         580 x 160 x 93 cm           Printer         790 x 200 x 210 cm         610 x 200 x 210 cm         580 x 160 x 93 cm           Weight         5000 KG         3600 KG         2200 KG           Power         UV Lamp         5000W         System         4500W           Requirment         Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp         Solder Lamp           Air         0.8 Mpa         Solder Lamp         Solder Lamp         Solder Lamp	Connectivity				
Dimensions           Printer         790 x 200 x 210 cm         610 x 200 x 210 cm         580 x 160 x 93 cm           Weight         5000 KG         3600 KG         2200 KG           Power         UV Lamp         5000W         system         4500W           Requirment         Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV Jamp         25A system, 25A UV Jamp	Dimensions           Printer         790 x 200 x 210 cm         610 x 200 x 210 cm         580 x 160 x 93 cm           Weight         5000 KG         3600 KG         2200 KG           Power         VV Lamp         5000W         System         4500W           Requirment         Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp         Sold Mpa           Air         0.8 Mpa         Sold Mpa         Sold Mpa		Fast stan	idard LISB Port		
Printer         790 x 200 x 210 cm         610 x 200 x 210 cm         580 x 160 x 93 cm           Weight         5000 KG         3600 KG         2200 KG           Power         VUV Lamp         5000W         state         state           System         4500W         Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp         state         50/60Hz. 25A system, 25A UV lamp	Printer         790 x 200 x 210 cm         610 x 200 x 210 cm         580 x 160 x 93 cm           Weight         5000 KG         3600 KG         2200 KG           Power         VUV Lamp         5000W         store           System         4500W         store         store           Air         0.8 Mpa         VUV Lamp         store         store		Tust stuff			
Power         UV Lamp       5000W         System       4500W         Requirment       Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz.         25A system, 25A UV lamp	Power       UV Lamp     5000W       System     4500W       Requirment     Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz.       25A system, 25A UV lamp       Air     0.8 Mpa		x 200 x 210 cm	610 x 200 x 210 cm	580 x 160 x 93 cm	
Power         UV Lamp       5000W         System       4500W         Requirment       Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz.         25A system, 25A UV lamp	Power       UV Lamp     5000W       System     4500W       Requirment     Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz.       25A system, 25A UV lamp       Air     0.8 Mpa	Weight	5000 KG	3600 KG	2200 KG	
UV Lamp5000WSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lamp	UV Lamp5000WSystem4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz. 25A system, 25A UV lampAir0.8 Mpa		5000 MG	5000 Hd	2200 110	
System4500WRequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz.25A system, 25A UV lamp	System     4500W       Requirment     Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz.       25A system, 25A UV lamp					
RequirmentInput voltage : 210 to 230VAC, 2 single phase, 50/60Hz.25A system, 25A UV lamp	Requirment       Input voltage : 210 to 230VAC, 2 single phase, 50/60Hz.         25A system, 25A UV lamp         Air       0.8 Mpa					
25A system, 25A UV lamp	25A system, 25A UV lamp       Air       0.8 Mpa		4500W			
	Air 0.8 Mpa	Requirment	Input vo	ltage : 210 to 230VAC, 2 sin	gle phase, 50/60Hz.	
Air 0.8 Mpa			25A syste	em, 25A UV lamp		
	Warranty One year	Air	0.8 Mpa			
Warranty One year		Warranty	One year			



Flex-Europa M.E.FZC Sharjah Airport Int'l Freezone Plot F3-17, P.O.Box 8509 PBU No. BS

@ info@flex-eu

Sharjah, UAE Ph: +971 6 55 78 200

00971 6 55 78 300

Dubai Production City PBU No. B31, P.O.Box 38

Dubai, UAE Ph: +971 4241 5414

rona me 🌐 www.fl



# XTRA 5000H High-res UV Hybrid Printer



## 1. Variable Color Configuration + Grayscale Print mode

Variable configuration to satisfy different customers for high speed, high resolution, white application request. True grayscale printing, drop size from 6pl to 18pl, which makes both solid color and color gradation available.

### 2. Anti-crash Sensor, Resume print after E-stop

The safety anti-crash sensor can detect the media circumstance beforehand and protect the print heads from a crush hazard. After that, you can resume printer, which will help you save media.

### 5. Vacuum Convey-belt System

Strong Vacuum to adsorb rigid material up to 51mm on the convey-belt, meanwhile easily prints flexible media as wall paper PVC,etc.

### 7.Belt automatic deviation correction Function

Belt auctomatic deviation correction device effctively avoids the convey-belt deviation, which makes the feeding perfectly straight.

# 3. Automatic Height Adjust System

The function makes the printer can print up to 5.1cm thick substrate.

### 4. Automatic Registration Pin System

Automatic registation pin system aid easy edge to edge printing, which simplifies the media location and ensure high precision printing output.

### 6. Industrial Take up & Feeding System

Rotate speed adjustable motor & pneumatic shaft can be adapted to various thickness substrates.

### 8. LED light box system

Built-in LED light strip for previewing light box performance as printing

Printer Model		XTRA 5000H	XTRA 3300H
Print Head	8~2	24 KM1024I print heads	4~15 KM1024I print heads
Drop Size		6 ~ 18 pic	olitre
Resolution		Up to 726 x 1	440 dpi
Productivity	Express	76 sqm/hr	76 sqm/hr
	Production Mode Quanlity Mode	60 sqm/hr 40 sqm/hr	60 sqm/hr 40 sqm/hr
	Ultra Quality	26 sqm/hr	26 sqm/hr
Ink Configuration	CMYK, CMYKW & C	CMYKWV	
Print Technology		ctricity inkjet mode, suppo	rt grayscale printing
Ink Types	UV LED inks		
Ink Cartridge Size	2.5 liter		
Image Process Software	Photoprint Flora Edition	on 19, Caldera & Onyx (O	ptional)
Color Management	ICC based color, adjust	stment curves, density adj	ustment
File Format	Tiff, Jpeg,Postscript, E	EPS, PDF,etc	
Media			
Handling	Vacuum table conve	y-belt movement, outreac	h tables extending media printing form
Rigid media support	Upto 50kg/sq.m.	500 x 250 cm	320 x 250 cm
Roll media support	40cm Diameter	500 cm	330 cm
Thickness	Up to 51mm		
Connectivity			
Interfaces	USB 3.0		
Curing System			
	Dual LED UV curing	system, separated adju	istable power.
Dimensions			
Printer	600x 155 x 160cm		
Shipping	620 x 187 x 206cm		
Weight			
		4900KG	3000KG
Operating Conditions			
Temperature	20 to 30°C		
Relative Humidity	35% - 65%, non-cond	lensing	
Electricity Request			
Power	8000W		
Requirement	Input voltage: 220 to	240VAC, single-phase, 50	0/60Hz,32Ax 2
Air	0.6.0.8М		
Morrophy	0.6-0.8Mpa		
Warranty	One year limited war	antu/Please contact your	local dealer for accurate data)
	One year minited Warr	anty(Flease contact your	



 Dubai
 Production
 City

 Plot F3-17, P.O.Box
 8509
 PBU No. B31, P.O.Box
 383816

 Sharjah, UAE
 Dubai, UAE
 Dubai, UAE

 Ph: +971 6 55 78 200
 Ph: +971 4241 5414
 Ph: +971 4241 5414

UAE

Ph: +971 6 55 78 200 Ph: +971 4241 5414 ♣ 00971 6 55 78 300 @ info@flex-europa.me ⊕ www.flex-europa.me

Ph: +962 6 4899 902

Fax: +962 6 4899 905

# XTRA 3300H High-res UV Hybrid Printer

Variable color configuration, standard 4 color puls white optional Grayscale print heads, variable drop size from 6 to 18pl Speed up to 76 sqm/hr Handles flexsible and rigid substrate up to 3.3m, and 5.1cm thick Vacuum belt driving with 8 vacuum zones White ink and CWC print capability solution



1. Variable Color Configuration + Grayscale Print mode Variable configuration to satisfy different customers for high speed, high resolution, white application request. True grayscale printing, drop size from 6pl to 18pl, which makes both solid color and color gradation available.

### 2. Anti-crash Sensor, Resume print after E-stop

The safety anti-crash sensor can detect the media circumstance beforehand and protect the print heads from a crush hazard. After that, you can resume printer, which will help you save media.

### 5. Vacuum Convey-belt System

Strong Vacuum to adsorb rigid material up to 51mm on the convey-belt, meanwhile easily prints flexible media as wall paper PVC,etc.

### 7.Belt automatic deviation correction Function

Belt auctomatic deviation correction device effctively avoids the convey-belt deviation, which makes the feeding perfectly straight.

3. Automatic Height Adjust System The function makes the printer can print up to 5.1cm thick substrate.

### 4. Automatic Registration Pin System

Automatic registation pin system aid easy edge to edge printing, which simplifies the media location and ensure high precision printing output.

### 6. Industrial Take up & Feeding System

Rotate speed adjustable motor & pneumatic shaft can be adapted to various thickness substrates.

Print	
Print Head	4~15 KM1024I print heads
Drop Size	6 ~ 18 picolitre
Resolution	Up to 726 x 1440 dpi
Productivity	Express 76 sqm/hr
	Production Mode 60 sqm/hr
	Quanlity Mode 40 sqm/hr
	Ultra Quality 26 sqm/hr
Ink Configuration	4C+White(Optional)
Print Technology	Piezoelectric inkjet, Grayscale Technology
Ink Types	LED inks
Ink Cartridge Size	2.5 liter
Image Process Software	Photoprint Flora Edition 12, Caldera 11& Onyx12(Optional)
Color Management	ICC based color, adjustment curves, density adjustment
File Format	Tiff, Jpeg,Postscript, EPS, PDF,etc
Media	
Handling	Vacuum table convey-belt movement rigid flexible printing capability material
Rigid media support	Standard convey-belt table support rigid materials up to 320cm width, 50kg/sqm
Roll media support	Max. print width up to 330cm, Weight 100kg, diameter 40cm
Thickness	Up to 51mm
Connectivity	
Interfaces	USB 3.0
Curing System	
	Dual LED UV curing system, separated adjustable power.
Dimensions	
Printer	600x 155 x 160cm
Shipping	620 x 187 x 206cm
Weight	
	3000KG
Operating Conditions	
Temperature	20 to 30°C
Relative Humidity	35% - 65%, non-condensing
Electricity Request	
Power	8000W
Requirement	Input voltage: 2.00 to 240VAC, single-phase, 50/60Hz,32Ax 2
Air	0.6-0.8Mpa
Aır	
Air Warranty	



# XTRA 2000HUV High-res UV Hybrid Printer

- Variable color configuration, standard 4 color puls white optional
- Grayscale print heads, variable drop size from 6 to 18pl
- Speed up to 100 sqm/hr
- Handles flexsible and rigid substrate up to 2m, and 5.1cm thick

RA2000HU

- Vacuum belt driving with 8 vacuum zones
- White ink and CWC print capability solution



- **Digital Printing System** 1. Variable Color Configuration + Grayscale Print mode
- 2. Anti-crash Sensor, Resume print after E-stop
- 3. Automatic Height Adjust System
- 4. Automatic Registration Pin System
- 5. Vacuum Convey-belt System
- 6. Industrial Take up & Feeding System
- 7.Belt automatic deviation correction Function

# **Dual Negative Pressure System**

Independent negative pressure system used for CMYK and White can effectively guarantee the continuity of print for all the colors.

# **Desicated White Ink**

XTRA2000HUV offers eight major utilizing white ink applications, which is the most common application for dark or transparent substrates to highlight and present the most vivid of graphic.Three layers printing (C+W+C) carry out synchronously double side printing on any transparent substrate

Print	
Print Head	4~12 KM1024I print heads
Drop Size	6 ~ 18 picolitre
Resolution	Up to 726 x 1440 dpi
Productivity	Production Mode100 sqm/hrQuality Mode70 sqm/hrUltra Quality50 sqm/hr
Ink Configuration	4, 6, 8 colors for option, C+M+Y+K, C+M+Y+K+W+V, C+M+Y+K+Lc+Lm
Print Technology	Piezoelectric inkjet, Grayscale Technology
Ink Types	LED UV inks
Ink Cartridge Size	1.5 liter
Image Process Software	Photoprint Flora Edition 12, Caldera 11& Onyx12(Optional)
Color Management	ICC based color, adjustment curves, density adjustment
File Format	Tiff, Jpeg,Postscript, EPS, PDF,etc
Media	
Handling	Vacuum table convey-belt movement, rigid flexible printing capability material
Rigid Media Support	Standard convey-belt table support rigid materials up to 200cm width
Rolling Media Support	Max. print width up to 330cm, diameter 30cm
Thickness	Up to 51mm
Connectivity	
Interfaces	USB 3.0
Curing System	Dual LED UV curing system, separated adjustable power.
Dimensions	
Printer	430x 100 x 155cm
Shipping	460 x 115 x 180cm
Weight	
	1500KG
Operating Conditions	20.45.20%0
Temperature	20 to 30°C
Relative Humidity Electricity Request	35% - 65%, non-condensing
Power	5000W
Requirement	Input voltage: 2.00 to 240VAC, single-phase, 50/60Hz,25A
Air	11pm Foldge, 2.00 to 270 4710, Single phase, 00/00112,207
	0.6-0.8Mpa
Warranty	
	One year limited warranty(Please contact your local dealer for accurate data)



### Flex-Europa M.E.FZC Sharjah Airport Int'I Freezone Plot F3-17, PO.Box 8509 Dubai Production City Plot No. B31, PO.Box 8539

 Plot F3-17, PO Box 8509
 PBU No. B31, PO Box 8509

 Sharjah, UAE
 Dubai, UAE

 Ph: +971 655 78 200
 Ph: +971 6241 5414

 ▲ 00971 6 55 78 300
 @ info@flex-europa.me 
 www.flex-europa.me

# TECHNICAL SPECIFICATIONS

Print head	4/6 GEN5 Print Heads(7pl)		
Productivity		6Heads	
roddodwity	Draft Mode (3pass)	71sgm/h	
	Speed(4pass)	55sqm/h	
	Production(6pass)	37sqm/h	
	Quality(8pass)	29sqm/h	
Print Resolution	Up to 605 x 1200dpi		
Technology	Piezoelectric inkjet, Graysc	ale mode	
Ink types	LED ink		
Ink Configuration	Standard CMYK		
Ink cartridge size	2.5L		
Rip software	Photoprint Flora Edition 12		
Color Management	ICC based color, adjustment curves, density adjustment		
File format	Tiff, Jpeg, Postscript, EPS, F	Tiff, Jpeg,Postscript, EPS, PDF,etc	
Media/Handling			
Handling	Industry Feeding & Take-up	Device with Tension system	
Roll media support	Support flexiable media up up to 100kg in weight	to 320cm wide, with a roll dimension 30cm,	
Connectivity			
Interfaces	High speed USB port(USB	3.0)	
Dimensions (I x w x h)			
Printer	492x96.5x155cm		
Shipping	503x100x170cm		
Weight			
	950KG		
Environment Condition			
Temperature	20 to 30 °C		
Relative Humidity	35%-65%, non-condensing		
Electricity Request			
Power Rate	2650W		
System	Input voltage: 200 to 240VA	C, single-phase, 50/60 Hz, 16A	
Warranty			

Standard 4 color, 4 level of Grayscale
 Industry Feeding and Take Up with Tension System
 Automatic Negative Pressure Adjustment System
 Platform Suction Adjustable System

5. High strength Steel Body Frame and High-precision linear Rail
6. Embedded man-printer Interaction System
7. Electronic Nozzles Flash Control



# Bits Description Descrip Description Desc

# XTRA320UV-G5



# Hi-Speed Large Format UV Printer

GEN5/7pl Print head, Variable drop size from 7pl to 21pl Standard 4 color, up to 6 print heads Draft qality up to 71 sqm/hr Printing width up to 3.20m Resolution up to 605x 1200dpi



# XTRA R-18

# **Hi-Res Large Format UV Printer**

Grayscale Printheads, variable drop size from 3.5 to 21pl Excellent coverage with strong, vibrant color Eight color ink set including CMYK Print color, white and clear together in one pass Flora spot color matching and Rip included



Print			
Print Head	6 G5 print heads		
Resolution	Up to 450 x 1200 dpi		
	pass		
Draductivity	4	45sqm/h	
Productivity	6	33sqm/h	
<u> </u>	8	24sqm/h	
Ink Configuration	C+M+Y+K		
Print Technology	Piezoelectric inkjet, Grays	scale Technology	
Ink Types	LED UV inks		
Ink Cartridge Size	1.5 liter		
Image Process Software	Photoprint Flora Edition 12	, Caldera 11& Onyx12(Optional)	
Color Management	ICC based color, adjustme	nt curves, density adjustment	
File Format	Tiff, Jpeg,Postscript, EPS,	Tiff, Jpeg,Postscript, EPS, PDF,etc	
Media			
Handling	Vacuum table convey-belt	movement rigid flexible printing capability material	
Rolling Media Support	Max. print width up to 1800	cm, diameter 30cm	
Connectivity			
Interfaces	USB 2.0		
Dimensions			
Printer	3210 x 1048 x 1420mm		
Shipping	3360 x1 1200 x 1590cm		
Weight			
	700KG		
Operating Conditions			
Temperature	15 to 32°C		
Relative Humidity	35% - 80%, non-condensir	35% - 80%, non-condensing	
Electricity Request			
Power	2500W	2500W	
Requirement	Input voltage: 220 to 240VA	Input voltage: 220 to 240VAC,50/60Hz	
Warranty			
	One year Limited warranty		

Variable Color Configuration + Grayscale Print mode
 Industry Feeding and Take Up with Tension System
 Automatic Negative Pressure Adjustment System
 Platform Suction Adjustable System

5. High strength Steel Body Frame and High-precision linear Rail6. Embedded man-printer Interaction System

7. Electronic Nozzles Flash Control









Better Products for a Better Future CoverPlus



**Bulk Ink Solution** 

EPSON ULTRACHROME

EPSON ULTRACHROME

RED

Epson Control Dashboard

1.5 Ltr Ink Pouches for high Print volume

PRECISIONCORE



	SC-S6060L	SC-580600L	
Printhead configuration	Dual PrecisionCore TFP printhead 360 x 2 nozzles each colour (x4)	Dual PrecisionCore TFP printhead 360 x 2 nozzles (x10)	
Maximum print speed (1 pass)	95.3m2/h <sup>-1</sup>	95.1m2/h <sup>1</sup>	
Minimum ink droplet volume	4.2	2pl	
Maximum print resolution	1440 x 14	440 dpi 1	
Media width (64 inch)	300 to 1,	626mm	
Maximum media thickness	1π	ım	
Roll outer diameter	Up to 2	50mm	
Reel outer diameter	Up to 200mm		
Roll weight	Up to 45kg		
Number of inks	2 x 4 colours (C,M,Y,K) 9/10 colours (C,M,Y,K, Lc, Lm, Lk, Or, Re + Mt or Wh)		
Ink pouch capacity	1.5lt	1.5lt, 500ml Metallic	
Software	Epson Edge Print		
Connectivity	USB: High-Speed USB 2.0 Ethernet: 100Base-TX/1000Base-T		
	W: 2,766mm	W: 2,766mm	
Dimensions	H: 1,338mm (covers closed) (max. 1,671mm for operation)	H: 1,338mm (covers closed) (max. 1,671mm for operation)	
	D: 972mm	D: 880mm	
	(max. 1,147mm for operation)	(max. 1,090mm for operation)	
Weight (excluding ink pouches/ including bulk ink solution)	336kg 328kg		
Voltage	AC 100-120V or 200-240V 50/60Hz		
Warranty	2 years onsite		
Noise level	59db		
Auto media setup	Yes		
Advanced Additional Drying System	Included Option		





 Dubai
 Production City

 Plot F3-17, P.O.Box 8509
 Dubai
 Production City

 Sharjah, UAE
 PBU No. B31, P.O.Box 383816
 Dubai, UAE

 Ph: +971 65 78 200
 Ph: +971 4241 5414

a 00971 6 55 78 300 @ info@flex-europa.me @ www.flex-europa.me



**Productive** inter SureColor SC-S60610 52 10 Colors





High quality Signage Printer SureColor SC-S40610



# **PRODUCT SPECIFICATIONS**

TECHNOLOGY Ink Technology	Ultrachrome® GS3
PRINT Colours	Black, Light Black, Metallic Silver, Cyan, Light Cyan, Yellow, Magenta, Light Magenta, Red, Orange, White, Cleaning liquid
Nozzle Configuration Minimum Droplet Size	360 Nozzles black, 360 Nozzles per colour 4.2 pl
PAPER / MEDIA HANDLING Print Margins Roll Media Compatible Paper Thickness Paper Formats Duplex	Mode 1: 5 mm (top), 3 mm (right), 5 mm (bottom), 3 mm (left) 0.1 mm - 1,000 mm 64 " (162.6 cm) No
GENERAL Energy Use Supply Voltage Product dimensions Product weight Sound Power Noise Level	800 W, 580 W (economy), 12 W (standby), 1.5 W (Power off) AC 100 V - 240 V, 50 Hz - 60 Hz 2,620 x 1,147 x 1,338 mm (Width x Depth x Height) 279 kg Operation: 7.7 B (A) Operation: 59 dB (A) - standby: 7.4 dB (A)
OTHER FEATURES Memory Emulations	Printer: 512 MB, Network: 128 MB ESC/P-R
OTHER Compatible Operating Systems	Windows 7, 8, 10
OTHER Warranty	24 months On site service Optional warranty extension available

# Discover a whole new range of creative applications with this precise, superior-quality and productive signage and display printer

Featuring the latest generation dual Epson PrecisionCore TFP printheads, the SC-S80610 produces outstanding output with superb colours and clarity. Working in tandem with new formulation Epson UltraChrome GS3 with Red inks, users can produce a wide range of highly accurate colours. Improving the quality on a range of substrates is possible thanks to the printers' Precision Dot highquality mode.







# Flex-Europa M.E.FZC FLEX-EUROPA 971 6 55 78 20

lo B31 PO Box 383816 00971 6 55 78 300



Surger and





# **PRODUCT SPECIFICATIONS**

TECHNOLOGY Ink Technology	Ultrachrome <sup>®</sup> DS
PRINT Colours Ink tank capacity Minimum Droplet Size	Black, Cyan, Yellow, Magenta 1,500 ml 5.3 pl, With Variable-Sized Droplet Technology

### PAPER / MEDIA HANDLING

Print Margins Roll Media Mode 1: 3 mm (top), 3 mm (right), 3 mm (bottom), 3 mm (left) Compatible Paper Thickness 0.08 mm - 0.5 mm Compatible Paper Weight75g/m<sup>2</sup> or heavier

### GENERAL

Energy Use	65 W, 20 W (economy), 3 W (standby), 0.4 W (Power off)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	1,608 x 1,128 x 917 mm (Width x Depth x Height)
Product weight	85 kg
Sound Power	Operation: 7.3 B (A)
Noise Level	Operation: 55.1 dB (A)

### **OTHER FEATURES**

OTHER

Warranty

Memory Printer: 512 MB, Network: 128 MB

OTHER Media Handling **Roll Paper** 

12 months On site service Optional warranty extension available



# Flex-Europa M.E.FZC Sharjah Airport Int'l Freezone Plot F3-17, P.O.Box 8509 Dubia Prov PBU No. E

Dubai Production City PBU No. B31, P.O.Box 383816 Dubai, UAE Ph: +971 4241 5414 Sharjah, UAE Ph: +971 6 55 78 200 🛔 00971 6 55 78 300 🛛 @ info@flex-europa.me 🌐 www.flex-europa.me



# SureColor SC-F6300

# Complete dye-sublimation package for creating high-quality textiles and promotional goods

The SureColor SC-F6200 is a professional digital dye sublimation roll-to-roll printer developed specifically for the production of high-quality printed textiles and promotional goods. Part of a complete Epson package, everything is made and supported by one manufacturer to ensure it all works seamlessly together.

44 inch dye sub Colors 



EPSON

13.00



# **DTG t-shirt** Printer

# SureColor SC-F2100

# The SureColor SC-F2000 is the first Direct-To-Garment (DTG) printer from Epson, offering a complete design and textile printing package.

You can now print directly onto fabric, thanks to the SureColor SC-F2000's new ink, design software and printhead. With low total cost of ownership, it is reliable and productive and is ideal for printing directly onto t-shirts and bags. With its UltraChrome DG ink and new software, this fabric printer gives you the opportunity to start making money fast.

# **PRODUCT SPECIFICATIONS**

## 

PAPER / MEDIA HANDL	ING	
Print Area	Large Platen (16"x20"/406x508mm), Medium Platen (14"x16"/356x406m (10"x12"/254x305mm), Sleeve Platen (4"x 4"/ 101 x 101mm)	ım), Small Platen
Compatible Substrate Thickness	up to 25 mm	
TECHNOLOGY Ink Technology	Ultrachrome <sup>®</sup> DG	
PRINT Colours Nozzle Configuration Ink tank capacity	Black, Cyan, Yellow, Magenta, White 720 Nozzles black, 720 Nozzles per colour, 720 Nozzles white x2 600 ml	Colors
GENERAL Energy Use Supply Voltage Product dimensions Product weight Sound Power Noise Level	52 W, 20 W (economy), 10 W (standby), 0.5 W (Power off) AC 100 V - 240 V, 50 Hz - 60 Hz 985 x 1,425 x 490 mm (Width x Depth x Height) 82 kg Operation: 5.7 B (A) Operation: 41 dB (A)	
NOISE LEVEL		

# **OTHER FEATURES**

Memory Printer: 512 MB, Network: 128 MB Recommended Substratecotton 100%, blended materials with a minimum of 50% cotton Maintenance system White ink circulation system, Automatic wet fabric wiper system Gap detection system LED gap sensor Direct print from USB Features

### OTHER Warranty

12 months On site service Optional warranty extension available



# Prints on black or white garments up to 25mm thick



# Flex-Europa M.E.FZC

Sharjah Airport Int'l Freezone Plot F3-17, P.O.Box 8509 Sharjah, UAE Ph: +971 6 55 78 200

00971 6 55 78 300

FLEX-EUROPF



# E-JELA320UV



# 3.2 m Pinch Roller RTR UV Printer

KONICA 1024 A Print heads, Variable droplet sie from 6pl Standard 4 Color, up to 10 print heads Draft quality upto 120 sqm/hr Printing width up to 3.20 m Resolution upto 2160 dpi

Page         Page         3pass         120m²/h         73m²/h           Generation         4pass         90m²/h         55m²/h	Speed	Production mode	High-precision mode
	6pass	60m²/h	36m²/h

Double four-color scheme (CMYK X 2 rows)

# TECHNICAL SPECIFICATIONS

Print	
Print Head	KONICA 1024i - 6pl / KONICA 1024A - 6pl
Max Print Resolution	2160 Dpi
Technology	Piezoelectric inkjet, Grayscale mode
Ink types	UV LED Ink
Ink Supply Method	Vaccum Negative Pressure with Automatic continuous ink supply
Printhead Configuration	Standard : CMYK ( Optional : CMYK+W , CMYK+LcLm )
Rip software	Photoprint ( optional : Onyx / Caldera )
Color Management	ICC based color, adjustment curves, density adjustment
File format	Tiff, Jpeg,Postscript, EPS, PDF,etc
Dimensions (I x w x h)	
Printer	4840 x 1320 x 1560 mm
Shipping	5000 x 1050 x 1630 mm
Weight	
Gross Weight	1135 Кg
Environment Condition	
Temperature	20 to 30 °C
Relative Humidity	35%-65%, non-condensing
Electricity Request	
Power Rate	2650W
System	Input voltage: 200 to 240VAC, single-phase, 50/60 Hz, 16A
Warranty	
	One year limited warranty. (please consult your local dealer for accurate data)



Flex-Europa M.E.FZC

UAE Sharjah Airport Int'l Freezone Plot F3-17, P.O.Box 8509 JORDAN

Ph: +962 6 4899 902

Fax: +962 6 4899 905

Sharjah, UAE Ph: +971 6 55 78 200 Dubai, UAE Ph: +971 4241 5414

Dubai Production City

PBU No. B31, P.O.Box 383816

4pass

6pass

Color white color scheme (CMYKW X 2 rows)

30m²/h

20m²/h

18m²/h

12m<sup>2</sup>/h

着 00971 6 55 78 300 🛛 @ info@flex-europa.me 🌐 www.flex-europa.me

# **E-JET** TEXTILE Direct Sublimation



Print Media: Mainly for based on polyester fabric material. Print direct on fabric without heating transfer process. This machine prints directly on fabric without heating transfer process. It can work continuously for 24 hours without corrugated.

# **PRODUCT SPECIFICATIONS**

Model	Ejet - CSP1600			
Print head	4 / 6 / 8 pcs Epson i3200Printhead			
Max Print Width	1.6 Meter			
Print Modes	360x1200 / 360 x 1800 / 720x1200 / 720x1800dpi			
	2 Pass / 3 Pass / 4 p	oass / 6 Pass	·	
Print Speed		4 Heads	6 Heads	8 Heads
	Production mode :	140 Sq.m / hr	170 Sq.m / hr	210 Sq.m / ł
	H Quality mode :		115 Sq.m / hr	145 Sq.m / ł
	H Pression mode :	70 Sq.m / hr	85 Sq.m / hr	105 Sq.m / ł
Colors	4 Colors / CMYK			
Ink type	Sublimation ink			
Media Type	Polyster			
Print Mode	One way / Two way			
Power Consumption	Preheating : 6.5 Kw ; Working : 4.5 Kw			
Power rating	220V ± 10% (AC 50 / 60 Hz ) ; 30A Single Phase			
Working Environment	Temperature:20-30	humidity:35%RH	I-65%RH	
Weight	Net: 800 Kg , Gross: 860 Kg			
Size	L3160*W1200*H138	0mm		

1. Printing speed, quality and stability is competitive to the Japanese similar piezoelctric Epson Printer; 2. Professional cloth feeding and take-up system, It's suitable for cloth without elasticity that can feed

- cloth stably ensure printing progress;
- 3. Constant temperature heating color development box, temperature rising quickly, good sealing ensure constant temperature;
- 4. Environmental smoke filtration system
- 5. Low ink level alarm system alert when inks runout in the Main ink tank.



Dubai Production City PBU No. B31, P.O.Box 383816

+971 4241 5414

Dubai, UAE



# **FE - UV6090**

High-Res Professional Small UV Flatbed Printer



Realize 360° rotary printing with the electric motor mover mug jig.



Independent ink cartridge Print height can be design, Intelligent alarm achieve 0 - 180 mm for ink tank level



Indipendent flash spray slot design

# FE-UV6090



el Number	FE - UV6090	
ing Size	600*870mm (When Print all-white,Color & Varnish at same time ) 600*900mm (When white & Color at same time )	
Head	EPSON F1080-A1	
Version	Color, white & V arnish	
ng Height	0-180mm	
der Material Diameter	Φ30-120mm(No varnish will be printed when choosing rotary mode)	
est Print Resolution	1440dpi(8pass)	
Mode	CM YKLcLm + W + V/ CM YKLcLm + W	
Software	Flexi Photo Print MiniUV Cloud Edition 19	
er Dimension	1620mm*1590mm*680mm(Length*Width*Height)	
er	AC220/110V±10,50HZ~60HZ	
hic Format	Tiff,Jpg,Eps,Pdf,Png,AI,Psd	
king Environment	Temperature:20°C-28°C ,Humidity:35%-65%	
	180KG	



Highe

Powe

Worl N.W.

> Sharjah Airport Int'l Freezone Plot F3-17, P.O.Box 8509 Sharjah, UAE Ph: +971 6 55 78 200

JORDAN

Ph: +962 6 4899 902

Dubai Production City PBU No. B31, P.O.Box 383816 Fax: +962 6 4899 905 Dubai, UAE Ph: +971 4241 5414

Flex-Europa M.E.FZC

00971 6 55 78 300

UAE

@ info@flex-europa.me 🕀 www.flex-europa.me

# **FE-Laminator**



FE-Laminator

### SINGLE HOT/COLD LAMINATOR

High-performance laminator suitable for industrial applications. It allows laminating, mounting and incapsulating prints, applying application tape and double-sided adhesive; compatible with all kinds of cold laminating film on the market.

# SUITABLE FOR:

**4**1

FE-Laminator

Printed exible materials **Rigid displays** Cardboard (packaging) Car wrapping Floor graphics **Backlit displays** Graphics for exhibitions, events Banner roll-up & Display pop-up Table displays Many more .....

915 0 Prints FE-Laminator Liner film laminating

O Professional sturdy and robust laminator designed to guarantee every day high quality results with great speed. DE4"ALUMINUM SHAFTS (total 5 shafts) for easy loading

Olt can support big and heavy rolls with diameter up to 200mm thanks to the increased distance between rollers and support shafts.

O Heated upper roller with preset electronic temperature regulation

Oldeal for mounting images on panels even of large dimensions, for

incapsulations or for applying at the same time a plastic Im and a double-

Intuitive set up parameters thanks to the user-friendly control panel.

D

OP

0

000

Od

and unloading of the rolls.

sided adhesive for mounting

- standard on HCS160 model(Room- 60°C)

Flatten bar Unfolding bar Linerless Film 0 6 Prints Take-up shaft Prints

K-Laminate



Liner

21

Linerless film laminating

Line

0 0

Take-up shaft.



Model	HCS160
Max laminating width	1620mm
Max laminating thickness	35mm
Max Speed	15m/min
Max temp	Room~60°C
Heating	Infrared
Preheating time	10~15min
Roller upgrade	Air cylinder
Power input	0.8-1.0kw/h
Volt	110/220V
Roller material	silicon
N.W	250kg



FLEX-EUROPF

Flex-Europa	M.E.	
Sharjah Airport Int'l Freezone Plot F3-17, P.O.Box 8509 Sharjah, UAE		

.FZC Dubai Production City PBU No. B31, P.O.Box 383816 Dubai, UAE Ph: +971 4241 5414

Ph: +971 6 55 78 200

🛔 00971 6 55 78 300 🛛 @ info@flex-europa.me 🤀 www.flex-europa.m

Linear guides Ensure Perfect Lifting of Rubber roller

Power Failure Protection Device

Automatic Holding Device

Easy Adjustable Blade Easy Blade Replacement

Lamination

# FLEX-EUROPA

# Flex-Europa M.E.FZC

 
 Sharjah Airport Int'l Freezone Piot F3-17, P.O. Box 8509 Sharjah, UAE
 Dubai Production City PBU No. B31, P.O.Box 383816 Dubai, UAE

 Ph: +971 65578 300
 Ph: +971 4241 5414

 00971 6 55 78 300
 @ info@flex-europa.me

# Smart Table

# FOR ALL SIZE PRINTS & KINDS OF BOARD

When it comes to improve through put and maximising your profit, you need tools your business can rely on. The FAYON Smart Table is your secret weapon when it comes to deliver timely graphic applications that your customers will love.



Whether you're premasking cut letters, mounting prints onto boards or laminating, the FAYON will help you do the job without wrinkles or bubbles resulting in a smooth finish everytime. Even oversize prints can be finished with ease. What's more, it can be run with one operator, making your shop more efficient!

### Mounting

It only takes one person to mount digital prints or adhesive stickers on to many form of substraights. Mount on foam board, corrugated panels, metal panels, banners and glass, all without bubbles.

### Laminating

FAYON smart table can also be used for post processing laminating in cold or heat assist modes.

### Work Station

Of course the Surface can also be used for any of your signage uses. Trimming graphics, doing layouts, weeding. FAYON smart table can be a great support for your shop in speeding up jobs and efficency.



Model FY-1325 最大覆膜面积 Max laminating size 1300/2500mm 最大覆膜厚度 Max laminating thickness 50mm 手动 Manual 覆膜方式 Operation type 胶辊提升方式 Roller upgrade Air cylinder 額定输入功率 Power input 0.8~1.0kw/h 气压调节范围 Pressure Range 0-0.8Mpa 机器重量 N.W. 380kgs



# <image>

Teatte

Toptek

100

# **PRODUCT SPECIFICATIONS**

Travelling area	132cm (w) x 254cm (w) x 20cm (H)
Table Size	122cm (w) x 244cm (L)
Transmission	X/Y Herion helical rack and pinion drive, Z ball screw drive
Table structure	T-slot vacuum table in four zone with butterfly valve
Spindle Power	6.0 KW
Spindle Speed	18000 - 26000 r/min
Moving Speed	40m/min
Drive and Motor	Stepper motor and driver
Working voltage	AC380V/3PH/50Hz, 32A
Control system	NC studio NK 105 control system

# Features

Italian 6.00KW HSD air cooling spindle

Japanese SHIMPO gear reducer

PMI Linear guide with dust proof and self lubrication

one set KVT3.140 BECKER vacuum pump

Stepping Motor and driver

NC studio NK105

Original Type 8 software

Taiwanese DELTA VFD-E inverter

One set of advertising tool

Warranty

One year

# **FE CNC NM-48** Professional CNC Machine

FE CNC used to cut, trim and shape awide variety of materials including wood, plastic, composites, foam, honecomb core and non-ferrous metals into flat dimensional shaped products. this fast accurate machine are used by a wide variety of manufacturing industries including Sign Making woodworking, plastic, Art & many more.

. . . . . .

Toptek

FLEX-EUROPA









Flex-Europa M.E.FZC

UAE

Dubai Production City PBU No. B31, P.O.Box 383816 Dubai, UAE Ph: +971 4241 5414 **JORDAN** Ph: +962 6 4899 902 Fax: +962 6 4899 905

Ph: +971 6 55 78 200

Sharjah Airport Int'l Freezone

Plot F3-17, P.O.Box 8509

Sharjah, UAE

@ info@flex-europa.me 🕀 www.flex-europa.me





